



Specifications Noxion LED Panel  
Louvre Excell G2 Gloss Reflector 34W  
3450lm - 830-840 CCT | 120x30cm -  
UGR <19 - Philips Xitanium Driver

[View Product](#)

General Information

|                          |                                                                                    |
|--------------------------|------------------------------------------------------------------------------------|
| SKU                      | 246170                                                                             |
| EAN                      | 8719157044301                                                                      |
| Brand                    | Noxion                                                                             |
| Manufacturer Name        | Noxion LED Louvre Excell G2. 34W 3000+4000K 1200 Polished Incl.Driver (2x28W eqv.) |
| Any Lamp all-in warranty | 6 Years                                                                            |
| Average Lifetime (h)     | 70000                                                                              |
| Series                   | Louvre Excell                                                                      |

Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 2x36                             |
| Wattage                     | 34                               |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Not Dimmable                     |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light colour options        | CCT                              |
| Luminous Flux (Lumen)       | 3450                             |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 101.5             |
| IP-rating                | IP20              |
| Impact Protection (IK)   | IK02 - 0.20 joule |
| Fixture Connection       | Terminal, 2-pole  |
| Finish of Reflector      | Gloss             |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                  |
|-----------------------|----------------------------------|
| Mounting Method       | Recessed                         |
| Unified Glare Rating  | < 19 - for offices and schools   |
| Optical Cover         | PET (Polyethylene Terephthalate) |
| Operating Temperature | -20 to +50                       |
| Emergency Lighting    | No Emergency Unit                |
| Colour of the Fixture | White                            |
| Housing               | Steel                            |
| Colour of material    | White                            |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |
| Height (mm)    | 55       |

## Sensor Information

Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process